

MATERIAL SAFETY DATA SHEET

MSDS Name: HI HEAT ALUMINUM
 MSDS Number: J-0521
 Version Number
 MSDS Date: MAY-01-2007
 Page Number: 1 of 6

myers 45170

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: HI HEAT ALUMINUM
 CAS Number: MIXTURE
 Hazard Ratings: Health: 2 Fire: 3 Reactivity: 0 PFI: B

Company Identification: Akron Paint & Varnish, Inc.
 DBA APV Engineered Coatings
 1390 Firestone Parkway
 Akron OH 44301

Contact: James K. Mosey
 Telephone/Fax: (330) 773-8911 (330) 773-1028
 Emergency Phone (24 Hour): EVENING ADMINISTRATOR
 (330) 773-8911
 Chemtec (24 Hour): (330) 773-8911

Product Class: PAINT
 Trade Name
 Product Code: J-0521
 DOT Hazard Class
 UN Number
 Shipping Name
 Technical Name

ADDITIONAL INFORMATION

SECTION II - INGREDIENT AND HAZARD INFORMATION

Ingredient Name	CAS Number	Percent	TSCA
* XYLENE HMIS Health: 2 Fire:3 Reactivity:0 PFI:H_____	1330-20-7	30 - 60	Y
* ETHYL BENZENE HMIS Health: 2 Fire:3 Reactivity:0 PFI: _____	100-41-4	7 - 13	Y
* TOLUENE HMIS Health: 2 Fire:3 Reactivity:1 PFI: _____	108-88-3	0.1 - 1.0	Y

MATERIAL SAFETY DATA SHEET

MSDS Name: HI HEAT ALUMINUM
MSDS Number: J-0521
Version Number
MSDS Date: MAY-01-2007
Page Number: 2 of 6

*** ALL Ingredients in this product are listed in the T.S.C.A. Inventory

ADDITIONAL INFORMATION

SECTION 313 SUPPLIER NOTIFICATION: THIS PRODUCT MAY CONTAIN TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT TO KNOW ACT OF 1986 AND 40 CFR 372 (NOTED BY THE * SYMBOL).

CAUTION: This product may become a dust nuisance when removed by sanding, abrading or sandblasting. Dust masks should be worn during these operations.

NE = not established NA = not available
NR = not regulated

THIS PRODUCT DOES NOT CONTAIN POLYCYCLIC ORGANIC MATERIAL SOLVENTS.

ALL COMPONENTS OF THIS MIXTURE ARE LISTED ON THE TSCA INVENTORY.

SECTION III - PHYSICAL DATA

Form:	LIQUID
Appearance/Color:	SILVER
pH Value:	0.
Boiling Range:	281-284 DEGS.
Vapor Pressure (mmHg):	0. @ 0.°F (-17.78°C)
Melting Point:	0.°F (-17.78°C)
Evaporation Rate:	
Vapor Density:	Heavier than air
Partition Coefficient	
% Volatile Weight	71.98%
% Volatile Volume	80.94%
Specific Gravity:	0.97
VOC	5.82
Molecular Weight:	
Heavy Elements (ppm)	0.

MSDS Name: HI HEAT ALUMINUM
MSDS Number: J-0521
Version Number
MSDS Date: MAY-01-2007
Page Number: 3 of 6

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flammability Class IC
Flash Range: 80 DEG F
Explosive Ranges: 1.9%
12.3%

EXTINGUISHING MEDIA:

Carbon Dioxide----Dry Chemical----Foam----Water Fog
Use water for cooling material stored in vicinity of fire.

SPECIAL FIREFIGHTING PROCEDURES:

Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode. Wear protective clothing.

UNUSUAL FIRE & EXPLOSION HAZARDS:

Vapors are heavier than air and may travel along the ground to an ignition source some distance from material handling point. Ignition sources include pilot lights, smoking, heaters, electric motors, sparks from electrical switches and static discharges.

CAUTION: Never use cutting torch on empty containers! Residual solvent vapor in empty container may explode. Application to hot surfaces requires special precautions. During emergency conditions, overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain Medical Attention.

SECTION V - HEALTH HAZARD DATA

Route	Species	Exposure and Dose
-------	---------	-------------------

PERMISSIBLE EXPOSURE LEVEL:

Refer to Section II

EFFECTS OF OVEREXPOSURE:

EYES: Can cause redness, irritation, swelling and blurred vision.

SKIN: Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis.

BREATHING: Excessive inhalation of vapors and/or spray mist can cause respiratory irritation, dizziness, weakness, fatigue, nausea, headache, unconsciousness and even asphyxiation.

MSDS Name: MI HEAT ALUMINUM
MSDS Number: J-0521
Version Number
MSDS Date: MAY-01-2007
Page Number: 4 of 6

SWALLOWING: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea; aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

FIRST AID:

EYES: Flush with large amounts of water for 15 minutes. Lift eyelids occasionally, get prompt medical attention.

SKIN: Wash thoroughly with soap and water, remove contaminated clothing promptly; wash clothing before reuse. Consult a physician if irritation persists.

SWALLOWING: Since this product may contain materials which can cause lung damage if aspirated into the lungs, the decision whether to induce vomiting must be made by a physician after careful consideration of all materials ingested.

INHALATION: Move affected person to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention. Consult a physician.

SECTION VI - REACTIVITY DATA

Stability: This product is stable
Hazardous Polymerization: Hazardous polymerization will not occur

INCOMPATIBILITY

Avoid contact with strong oxidizers (e.g. nitric acid)

CONDITIONS TO AVOID:

Keep away from heat and open flame.

HAZARDOUS DECOMPOSITION PRODUCTS:

May form carbon monoxide and dioxide, various hydrocarbons, etc.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

SMALL SPILL: Absorb liquid with rags, floor absorbent, vermiculite or other absorbent material and transfer to hood.

LARGE SPILL: Eliminate all ignition sources---dike area of spill to prevent spreading---ventilate area if indoors---pump liquid into salvage tank---remaining liquid may be taken up with sand, floor absorbent or other absorbent material and shoveled into containers---prevent run-off to sewers and bodies of water---notify proper authorities as required by local, state and federal regulations.

MATERIAL SAFETY DATA SHEET

MSDS Name: HI HEAT ALUMINUM
 MSDS Number: J-0521
 Version Number
 MSDS Date: MAY-01-2007
 Page Number: 5 of 6

WASTE DISPOSAL METHOD:

Dispose of in accordance with federal, state and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
\$ XYLENE	100.00 PPM	N/est	150.00 PPM	N/est	100.00 PPM
\$ ETHYL BENZENE	100.00 PPM	N/est	125.00 PPM	N/est	100.00 PPM
\$ TOLUENE	50.00 PPM	N/est	N/est	150.00 PPM	100.00 PPM

RESPIRATORY PROTECTION:

In outdoor or open areas with unrestricted ventilation approved chemical/mechanical filters designed to remove a combination of particulates and vapor.

VENTILATION:

Provide sufficient ventilation in volume and pattern to keep air contaminant concentration below current applicable OSHA permissible exposure limit or ACGIH TLV limit, and volatiles below lower explosive limit. Heavy solvent vapors should be removed from the lower levels of area, and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered. Remove decomposition products formed during welding or flame cutting of surfaces coated with this product. For baking finishes - vent vapors emitted on heating.

PROTECTIVE GLOVES:

Wear resistant gloves such as: nitrile rubber

EYE PROTECTION:

Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA regulations also permit other types of safety glasses. (Consult your safety equipment supplier)

OTHER PROTECTIVE EQUIPMENT:

Normal protective clothing. Wash contaminated clothing before

MSDS Name: HI HEAT ALUMINUM
 MSDS Number: J-0521
 Version Number
 MSDS Date: MAY-01-2007
 Page Number: 6 of 6

reuse.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:
 Do not drop containers. Avoid heat, sparks, and open flame.
 Store large quantities only in buildings designed to comply
 with OSHA 1910.106. Never use pressure to empty. Avoid breath-
 ing sanding dust. Do not handle until the manufacturers
 safety precautions have been read and understood.

OTHER PRECAUTIONS:
 The information accumulated herein is believed to be accurate
 but is not warranted to be whether originating with the company
 or not. Recipients are advised to confirm in advance of need
 that the information is current, applicable, and suitable to
 their circumstances.

SECTION X - ADDITIONAL REGULATORY INFORMATION

SARA TITLE III SECTION 313:
 This product contains the following toxic chemicals subject to the
 reporting requirements of Section 313 of the Emergency Planning and
 Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
* XYLENE	1330-20-7	53.13
* ETHYL BENZENE	100-41-4	12.62

--PROP 65 (TERATOGEN)
 WARNING: This product contains a chemical known to the state of
 California to cause birth defects or other reproductive harm.

Ingredient Name	CAS Number	Percent
* TOLUENE	108-88-3	0.66

SARA TITLE III SECTION 313:

PROP 65 (CARCINOGEN):

MATERIAL SAFETY DATA SHEET

MSDS Name: HI HEAT ALUMINUM

MSDS Number: J-0521

Version Number

MSDS Date: MAY-01-2007

Page Number: 7 of 6

PROP 65 (TERATOGEN):

PROP 65 (BOTH CARCINOGEN AND TERATOGEN):