

## Safety Data Sheet

### Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

#### 1.1 Product identifier

- Product Name** • **Bead Sealer**
- Product Code** • **94-394**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

- Relevant identified use(s)** • Tire repair surface preparation

#### 1.3 Details of the supplier of the safety data sheet

- Manufacturer** • Patch Rubber Company  
100 Patch Rubber Road  
Weldon, NC 27890  
United States

**Telephone (General)** • (252)-536-2574

- Responsible party** • Christian Gimenez  
Intertek Analytical Services France  
France

**Telephone (Technical)** • 33 (0) 6 07 11 22 15

#### 1.4 Emergency telephone number

- Manufacturer** • 1-800-424-9300 - CHEMTREC
- Manufacturer** • +1 703-527-3887 - CHEMTREC - Outside USA & CANADA (collect calls accepted)

### Section 2: Hazards Identification

#### EU/EEC

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]  
According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

#### 2.1 Classification of the substance or mixture

- CLP**
- Flammable Liquids 2 - H225
  - Skin Irritation 2 - H315
  - Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336
  - Hazardous to the aquatic environment Chronic 1 - H410
  - Hazardous to the aquatic environment Acute 1 - H400
- DSD/DPD**
- Highly Flammable (F)
  - Irritant (Xi)
  - Harmful (Xn)
  - Dangerous to the Environment (N)
  - R11, R50, R53, R38, R67

## 2.2 Label Elements

### CLP

#### DANGER



- H225 - Highly flammable liquid and vapour
- H315 - Causes skin irritation
- H336 - May cause drowsiness or dizziness
- H400 - Very toxic to aquatic life
- H410 - Very toxic to aquatic life with long lasting effects

### Precautionary statements

- Prevention**
- P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
  - P273 - Avoid release to the environment.
  - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
  - P331 - Do NOT induce vomiting.
- Storage/Disposal**
- P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

### DSD/DPD



- Risk phrases**
- R11 - Highly flammable.
  - R38 - Irritating to skin.
  - R67 - Vapours may cause drowsiness and dizziness.
  - R50 - Very toxic to aquatic organisms.
  - R53 - May cause long-term adverse effects in the aquatic environment.
- Safety phrases**
- S2 - Keep out of reach of children.
  - S9 - Keep container in a well ventilated place
  - S16 - Keep away from sources of ignition - No Smoking.
  - S29 - Do not empty into drains.
  - S33 - Take precautionary measures against static discharges.
  - S60 - This material and its container must be disposed of as hazardous waste.
  - S61 - Avoid release to the environment. Refer to special instructions/ Safety Data Sheets.
  - S62 - If swallowed, do not induce vomiting. Seek medical advice immediately and show the container or label.

## 2.3 Other Hazards

- CLP**
- According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.  
This material contain less than 0.1% Benzene therefore the carcinogen and mutagen classifications listed in Annex VI are not applicable.
- DSD/DPD**
- According to European Directive 1999/45/EC this preparation is not considered dangerous.  
This material contain less than 0.1% Benzene therefore the carcinogen and mutagen classifications listed in Annex I are not applicable.

## UN GHS

### According to Third Revised Edition

## 2.1 Classification of the substance or mixture

- UN GHS**
- Flammable Liquids 2 - H225
  - Skin Irritation 2 - H315

Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336  
 Hazardous to the aquatic environment Acute 1 - H400  
 Hazardous to the aquatic environment Chronic 1 - H410

## 2.2 Label elements

### UN GHS

#### DANGER



- H225 - Highly flammable liquid and vapour  
 H315 - Causes skin irritation  
 H336 - May cause drowsiness or dizziness  
 H400 - Very toxic to aquatic life  
 H410 - Very toxic to aquatic life with long lasting effects

### Precautionary statements

- Prevention**
- P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
  - P235 - Keep cool.
  - P243 - Take precautionary measures against static discharge.
  - P240 - Ground and/or bond container and receiving equipment.
  - P242 - Use only non-sparking tools.
  - P241 - Use explosion-proof - electrical, ventilating and/or lighting equipment.
  - P271 - Use only outdoors or in a well-ventilated area.
  - P233 - Keep container tightly closed.
  - P261 - Avoid breathing dust, fume, gas, mist, vapours and/or spray.
  - P280 - Wear protective gloves and eye/face protection , .
  - P285 - In case of inadequate ventilation wear respiratory protection.
  - P264 - Wash thoroughly after handling.
  - P273 - Avoid release to the environment.
- Response**
- P370+P378 - In case of fire: Use appropriate media for extinction.
  - P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
  - P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
  - P302+P352 - IF ON SKIN: Wash with plenty of soap and water.
  - P362 - Take off contaminated clothing and wash before reuse.
  - P332+P313 - If skin irritation occurs: Get medical advice/attention.
  - P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
  - P331 - Do NOT induce vomiting.
  - P391 - Collect spillage.
- Storage/Disposal**
- P403+P235 - Store in a well-ventilated place. Keep cool.
  - P405 - Store locked up.
  - P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## 2.3 Other hazards

### UN GHS

- According to the Globally Harmonized Standard for Classification and Labeling (GHS) this product is considered hazardous.

## United States (US)

According to OSHA 29 CFR 1910.1200 HCS

### 2.1 Classification of the substance or mixture

#### OSHA HCS

- Flammable Liquid  
 Flammable/Combustible Class IB  
 Irritant  
 Target Organ Effects - Central Nervous System (CNS)

### 2.2 Label elements

**OSHA HCS**

- Not required

**2.3 Other hazards**

**OSHA HCS**

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

**Canada**

**According to WHMIS**

**2.1 Classification of the substance or mixture**

**WHMIS**

- Flammable Liquids - B2  
Other Toxic Effects - D2B

**2.2 Label elements**

**WHMIS**




- Flammable Liquids - B2  
Other Toxic Effects - D2B

**2.3 Other hazards**

**WHMIS**

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

**2.4 Other information**



See Section 12 for Ecological Information.

**Section 3 - Composition/Information on Ingredients**

**3.1 Substances**

- Material does not meet the criteria of a substance according to United Nations Globally Harmonized System of Classification and Labelling of Chemicals (GHS)  
Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

**3.2 Mixtures**

Hazardous Components					
Chemical Name	Identifiers	%(weight)	LD50/LC50	Classifications According to Regulation/Directive	Comments
	CAS:64742-49-			UN GHS: Flam Liq 2; Asp. 1; Skin Irrit. 2; STOT SE 3: Narc.; Aquatic Acute 1; Aquatic Chronic 1;	

Naphtha (petroleum), hydrotreated light	0 <b>EC Number:</b> 265-151-9	60% TO 100%	NDA	<b>EU DSD/DPD:</b> Annex I - F; R11 Xi; R38 N; R50 R53 Xn; R65 R67 <b>EU CLP:</b> Annex VI - Flam. Liq. 2, H225; Asp. Tox. 1, H305; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 1, H400; Aquatic Chronic 1, H410	NDA
Carbon Black	<b>CAS:</b> 1333-86-4 <b>EC Number:</b> 215-609-9	1% TO 5%	Ingestion/Oral-Rat LD50 · >15400 mg/kg Skin-Rabbit LD50 · >3 g/kg	<b>UN GHS:</b> STOT RE 1, Carc. 2 <b>EU DSD/DPD:</b> Self classified - Carc. 3 R40 <b>EU CLP:</b> Self classified - Carc. 2 H351	Will not be released in final product
Zinc oxide	<b>CAS:</b> 1314-13-2 <b>EC Number:</b> 215-222-5	0.5% TO 1.5%	Ingestion/Oral-Mouse LD50 · 7950 mg/kg	<b>UN GHS:</b> Data lacking <b>EU DSD/DPD:</b> Annex I - N; R50-53 <b>EU CLP:</b> Annex VI - Aquatic Acute 1 H400; Aquatic Chronic H410	NDA
Fuels, diesel, No. 2	<b>CAS:</b> 68476-34-6 <b>EC Number:</b> 270-676-1	0.1% TO 1.5%	NDA	<b>UN GHS:</b> Data Lacking <b>EU DSD/DPD:</b> Annex I - Carc.Cat.3; R40 <b>EU CLP:</b> Annex VI - Carc. 2, H351	NDA
Benzanilide, 2',2''-dithiobis-	<b>CAS:</b> 135-57-9 <b>EINECS:</b> 205-201-9	0.02% TO 0.024%	Ingestion/Oral-Rat LD50 · >4 g/kg	<b>UN GHS:</b> Skin Sens. 1 <b>EU DSD/DPD:</b> Self Classified - R43 <b>EU CLP:</b> Self Classified - Skin Sens. 1, H317	NDA

See Section 11 for Toxicological Information.

## Section 4 - First Aid Measures

### 4.1 Description of first aid measures

#### Inhalation

- Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing.

#### Skin

- In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention.

#### Eye

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

#### Ingestion

- Do NOT induce vomiting. If person is drowsy or unconscious and vomiting, place on the left side with head down. Seek medical attention.

### 4.2 Most important symptoms and effects, both acute and delayed

- Refer to Section 11 - Toxicological Information.

### 4.3 Indication of any immediate medical attention and special treatment needed

#### Notes to Physician

- Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to the material.

See Section 2 for Potential Health Effects.

## Section 5 - Firefighting Measures

### 5.1 Extinguishing media

**Suitable Extinguishing Media** ● Carbon dioxide (CO<sub>2</sub>), water fog, dry chemical or chemical foam.

**Unsuitable Extinguishing** ● Avoid the use of streaming water, as this may spread the fire.

**Media****5.2 Special hazards arising from the substance or mixture****Unusual Fire and Explosion Hazards**

- **HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Extremely flammable liquid and vapor. Vapors may form explosive mixtures with air. Vapor explosion hazard indoors, outdoors or in sewers. Vapors may travel to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

**Hazardous Combustion Products**

- Smoke, soot, fumes or vapors, oxides of carbon.

**5.3 Advice for firefighters**

- Structural firefighters' protective clothing will only provide limited protection. Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Wear positive pressure self-contained breathing apparatus (SCBA). Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

**Section 6 - Accidental Release Measures****6.1 Personal precautions, protective equipment and emergency procedures****Personal Precautions**

- Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Emergency Procedures**

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Keep out of low areas. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

**6.2 Environmental precautions**

- Avoid run off to waterways and sewers.

**6.3 Methods and material for containment and cleaning up****Containment/Clean-up Measures**

- Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

**6.4 Reference to other sections**

- Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

**Section 7 - Handling and Storage****7.1 Precautions for safe handling****Handling**

- Keep away from heat and ignition sources – No Smoking. Product can accumulate static charge by flow or agitation. Bond and ground equipment when transferring from one vessel to another. Empty containers retain product residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks or other ignition sources. They may explode and cause injury or death. Use only with adequate ventilation. Do not enter confined spaces such as tanks or pits without following proper entry procedures.

**7.2 Conditions for safe storage, including any incompatibilities**

**Storage**

- Store in a cool/low-temperature, well-ventilated place away from heat and ignition sources. Keep container closed when not in use. Keep away from incompatible materials.

**Incompatible Materials or Ignition Sources**

- Keep away from heat, ignition sources oxidizers and strong acids.

**7.3 Specific end use(s)**

- Refer to Section 1.2 - Relevant identified uses.

**Section 8 - Exposure Controls/Personal Protection****8.1 Control parameters**

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	Europe	France
Methylcyclohexane (108-87-2)	TWAs	400 ppm TWA	400 ppm TWAEV; 1600 mg/m3 TWAEV	400 ppm TWAEV; 1610 mg/m3 TWAEV	Not established	400 ppm VME; 1600 mg/m3 VME
3-Methylhexane (589-34-4)	STELs	500 ppm STEL	Not established	Not established	Not established	Not established
	TWAs	400 ppm TWA	Not established	Not established	Not established	Not established
Hexane, 2-methyl- (591-76-4)	STELs	500 ppm STEL	Not established	Not established	Not established	Not established
	TWAs	400 ppm TWA	Not established	Not established	Not established	Not established
Pentane, 2,3-dimethyl- (565-59-3)	STELs	500 ppm STEL	Not established	Not established	Not established	Not established
	TWAs	400 ppm TWA	Not established	Not established	Not established	Not established
Ethylbenzene (100-41-4)	STELs	125 ppm STEL	125 ppm STEV; 540 mg/m3 STEV	125 ppm STEV; 543 mg/m3 STEV	Not established	100 ppm VLCT (restrictive limit); 442 mg/m3 VLCT (restrictive limit)
	TWAs	100 ppm TWA	100 ppm TWAEV; 435 mg/m3 TWAEV	100 ppm TWAEV; 434 mg/m3 TWAEV	Not established	20 ppm VME (restrictive limit); 88.4 mg/m3 VME (restrictive limit)
Benzene (71-43-2)	STELs	2.5 ppm STEL	2.5 ppm STEV (applies to workplaces to which the designated substance regulation does not apply); 2.5 ppm STEV (designated substances regulation)	5 ppm STEV; 15.5 mg/m3 STEV	Not established	Not established
	TWAs	0.5 ppm TWA	0.5 ppm TWAEV (applies to workplaces to which the designated substance regulation does not apply); 0.5 ppm TWAEV (designated substance regulation)	1 ppm TWAEV; 3 mg/m3 TWAEV	Not established	1 ppm VME (restrictive limit); 3.25 mg/m3 VME (restrictive limit)
	TWAs	10 ppm TWA	10 ppm TWAEV; 30 mg/m3 TWAEV	10 ppm TWAEV; 30 mg/m3 TWAEV	Not established	10 ppm VME (indicative limit); 31 mg/m3 VME

Propionic acid (79-09-4)						(indicative limit)
	STELs	Not established	Not established	Not established	Not established	20 ppm VLCT (indicative limit); 62 mg/m <sup>3</sup> VLCT (indicative limit)
Kaolin (1332-58-7)	TWAs	2 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable fraction)	2 mg/m <sup>3</sup> TWAEV (containing no asbestos and less than 1% crystalline silica, respirable)	5 mg/m <sup>3</sup> TWAEV (respirable dust, containing no asbestos and less than 1% crystalline silica)	Not established	10 mg/m <sup>3</sup> VME
Toluene (108-88-3)	STELs	Not established	Not established	Not established	100 ppm STEL; 384 mg/m <sup>3</sup> STEL	100 ppm VLCT (restrictive limit); 384 mg/m <sup>3</sup> VLCT (restrictive limit)
	TWAs	20 ppm TWA	20 ppm TWAEV	50 ppm TWAEV; 188 mg/m <sup>3</sup> TWAEV	50 ppm TWA; 192 mg/m <sup>3</sup> TWA	50 ppm VME (restrictive limit); 192 mg/m <sup>3</sup> VME (restrictive limit)
Fuels, diesel, No. 2 (68476-34-6)	TWAs	100 mg/m <sup>3</sup> TWA (as total hydrocarbons, inhalable fraction and vapor)	100 mg/m <sup>3</sup> TWAEV (aerosol and vapour, as total hydrocarbons)	Not established	Not established	Not established
Calcium silicate (1344-95-2)	TWAs	10 mg/m <sup>3</sup> TWA (synthetic nonfibrous, particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m <sup>3</sup> TWAEV (total dust)	10 mg/m <sup>3</sup> TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)	Not established	Not established
Zinc oxide (1314-13-2)	STELs	10 mg/m <sup>3</sup> STEL (respirable fraction)	10 mg/m <sup>3</sup> STEV (respirable)	10 mg/m <sup>3</sup> STEV (fume)	Not established	Not established
	TWAs	2 mg/m <sup>3</sup> TWA (respirable fraction)	2 mg/m <sup>3</sup> TWAEV (respirable)	5 mg/m <sup>3</sup> TWAEV (fume); 10 mg/m <sup>3</sup> TWAEV (total dust, containing no asbestos and less than 1% crystalline silica)	Not established	5 mg/m <sup>3</sup> VME (fume); 10 mg/m <sup>3</sup> VME (dust)
Carbon Black (1333-86-4)	TWAs	3.5 mg/m <sup>3</sup> TWA	3.5 mg/m <sup>3</sup> TWAEV	3.5 mg/m <sup>3</sup> TWAEV	Not established	3.5 mg/m <sup>3</sup> VME
Heptane (142-82-5)	STELs	500 ppm STEL	500 ppm STEV; 2045 mg/m <sup>3</sup> STEV	500 ppm STEV; 2050 mg/m <sup>3</sup> STEV	Not established	500 ppm VLCT (restrictive limit); 2085 mg/m <sup>3</sup> VLCT (restrictive limit)
	TWAs	400 ppm TWA	400 ppm TWAEV; 1635 mg/m <sup>3</sup> TWAEV	400 ppm TWAEV; 1640 mg/m <sup>3</sup> TWAEV	Not established	400 ppm VME (restrictive limit); 1668 mg/m <sup>3</sup> VME (restrictive limit)
<b>Exposure Limits/Guidelines (Con't.)</b>						
	<b>Result</b>	<b>Italy</b>		<b>NIOSH</b>		<b>OSHA</b>
Methylcyclohexane (108-87-2)	TWAs	Not established		400 ppm TWA; 1600 mg/m <sup>3</sup> TWA		500 ppm TWA; 2000 mg/m <sup>3</sup> TWA



Ethylbenzene (100-41-4)	STELs	200 ppm STEL; 884 mg/m <sup>3</sup> STEL	125 ppm STEL; 545 mg/m <sup>3</sup> STEL	Not established
	TWAs	100 ppm TWA; 442 mg/m <sup>3</sup> TWA	100 ppm TWA; 435 mg/m <sup>3</sup> TWA	100 ppm TWA; 435 mg/m <sup>3</sup> TWA
Benzene (71-43-2)	TWAs	1 ppm TWA; 3.25 mg/m <sup>3</sup> TWA	0.1 ppm TWA	10 ppm TWA (applies to industry segments exempt from the benzene standard at 29 CFR 1910.1028); 1 ppm TWA
	Ceilings	Not established	Not established	25 ppm Ceiling
	STELs	Not established	1 ppm STEL	5 ppm STEL (see 29 CFR 1910.1028)
Propionic acid (79-09-4)	STELs	20 ppm STEL; 62 mg/m <sup>3</sup> STEL	15 ppm STEL; 45 mg/m <sup>3</sup> STEL	Not established
	TWAs	10 ppm TWA; 31 mg/m <sup>3</sup> TWA	10 ppm TWA; 30 mg/m <sup>3</sup> TWA	Not established
Kaolin (1332-58-7)	TWAs	Not established	10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Toluene (108-88-3)	TWAs	192 ppm TWA; 50 mg/m <sup>3</sup> TWA	100 ppm TWA; 375 mg/m <sup>3</sup> TWA	200 ppm TWA
	Ceilings	Not established	Not established	300 ppm Ceiling
	STELs	Not established	150 ppm STEL; 560 mg/m <sup>3</sup> STEL	Not established
Calcium silicate (1344-95-2)	TWAs	Not established	10 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable dust)	15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
Zinc oxide (1314-13-2)	TWAs	Not established	5 mg/m <sup>3</sup> TWA (dust and fume)	5 mg/m <sup>3</sup> TWA (fume); 15 mg/m <sup>3</sup> TWA (total dust); 5 mg/m <sup>3</sup> TWA (respirable fraction)
	Ceilings	Not established	15 mg/m <sup>3</sup> Ceiling (dust)	Not established
	STELs	Not established	10 mg/m <sup>3</sup> STEL (fume)	Not established
Carbon Black (1333-86-4)	TWAs	Not established	3.5 mg/m <sup>3</sup> TWA; 0.1 mg/m <sup>3</sup> TWA (carbon black in presence of polycyclic aromatic hydrocarbons, as PAH)	3.5 mg/m <sup>3</sup> TWA
Heptane (142-82-5)	TWAs	500 ppm TWA; 2085 mg/m <sup>3</sup> TWA	85 ppm TWA; 350 mg/m <sup>3</sup> TWA	500 ppm TWA; 2000 mg/m <sup>3</sup> TWA
	Ceilings	Not established	440 ppm Ceiling (15 min); 1800 mg/m <sup>3</sup> Ceiling (15 min)	Not established

## 8.2 Exposure controls

### Engineering Measures/Controls

- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable exposure limit values.

### Personal Protective Equipment

**Pictograms****Respiratory**

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced.

**Eye/Face**

- Wear safety goggles.

**Hands**

- Wear protective gloves -neoprene, butyl or nitrile rubber with cuffs.

**Skin/Body**

- Where extensive dermal exposure may be expected, either a chemical suit or chemical apron will be needed.

**General Industrial Hygiene Considerations**

- Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

**Environmental Exposure Controls**

- Follow best practice for site management and disposal of waste. Avoid release to the environment.

**Key to abbreviations**

ACGIH = American Conference of Governmental Industrial Hygiene

NIOSH = National Institute of Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

TWAEV = Time-Weighted Average Exposure Value

STEL = Short Term Exposure Limits are based on 15-minute exposures

VME = Valeur Moyenne d'Exposition is the maximum permissible concentration for a work day

STEV = Short Term Exposure Value

VLCT = Valeurs limites d'exposition à court terme is the short-term exposure limit based on 15-minute exposure.

MSHA = Mine Safety and Health Administration

**Section 9 - Physical and Chemical Properties****9.1 Information on Physical and Chemical Properties**

Material Description			
Physical Form	Liquid	Appearance/Description	Black flammable liquid with a hydrocarbon odor.
Color	Black	Odor	Hydrocarbon
Taste	Data lacking	Particulate Type	Not relevant
Particulate Size	Not relevant	Aerosol Type	Not relevant
Odor Threshold	Data lacking	Physical and Chemical Properties	Data lacking
General Properties			
Boiling Point	93.3 C(199.94 F)	Melting Point	Data lacking
Decomposition Temperature	Data lacking	Heat of Decomposition	Data lacking
pH	Data lacking	Specific Gravity/Relative Density	0.74 Water=1
Density	6.15 lbs/gal	Bulk Density	Data lacking
Water Solubility	Insoluble	Solvent Solubility	Data lacking
Viscosity	Not relevant	Explosive Properties	Classification criteria not met.
Oxidizing Properties:	Classification criteria not met.		
Volatility			
Vapor Pressure	45 mmHg (torr) @ 20 C(68 F)	Vapor Density	3.5 Air=1

Evaporation Rate	4.2 n-Butyl Acetate = 1	VOC (Wt.)	Data lacking
VOC (Vol.)	590 g/L	Volatiles (Wt.)	Data lacking
Volatiles (Vol.)	Data lacking		
<b>Flammability</b>			
Flash Point	-10 C(14 F)	UEL	7 %
LEL	1 %	Autoignition	223 C(433.4 F)
Self-Accelerating Decomposition Temperature (SADT)	Data lacking	Heat of Combustion ( $\Delta H_c$ )	Data lacking
Burning Time	Data lacking	Flame Duration	Data lacking
Flame Height	Data lacking	Flame Extension	Data lacking
Ignition Distance	Data lacking	Flammability (solid, gas)	Data lacking
<b>Environmental</b>			
Half-Life	Data lacking	Octanol/Water Partition coefficient	Data lacking
Coefficient of water/oil distribution	Data lacking	Bioaccumulation Factor	Data lacking
Bioconcentration Factor	Data lacking	Biochemical Oxygen Demand BOD/BOD5	Data lacking
Chemical Oxygen Demand	Data lacking	Persistence	Data lacking
Degradation	Data lacking		

## 9.2 Other Information

- No additional physical and chemical parameters noted.

## Section 10: Stability and Reactivity

### 10.1 Reactivity

- No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

- Stable under normal temperatures and pressures.

### 10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

### 10.4 Conditions to avoid

- High temperatures, sparks, open flames and live electrical circuits.

### 10.5 Incompatible materials

- Oxidizing agents, strong acids.

### 10.6 Hazardous decomposition products

- In case of fire oxides of carbon, hydrocarbons, fumes or vapors, soot and smoke may be produced.

## Section 11 - Toxicological Information

## 11.1 Information on toxicological effects

GHS Properties	Classification
Acute toxicity	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Skin corrosion/Irritation	EU/CLP • Skin Irritation 2 UN GHS • Skin Irritation 2
Serious eye damage/Irritation	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Skin sensitization	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Respiratory sensitization	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Aspiration Hazard	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Carcinogenicity	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Germ Cell Mutagenicity	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
Toxicity for Reproduction	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met
STOT-SE	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects UN GHS • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
STOT-RE	EU/CLP • Classification criteria not met UN GHS • Classification criteria not met

### Target Organs

- Central Nervous System (CNS)

### Route(s) of entry/exposure

- Inhalation, Skin, Eye, Ingestion

### Potential Health Effects

#### Inhalation

##### Acute (Immediate)

- May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death. Intentional concentration and inhalation of vapors of this material may lead to nervous system damage.

##### Chronic (Delayed)

- No data available.

#### Skin

##### Acute (Immediate)

- Causes skin irritation.

##### Chronic (Delayed)

- Repeated and prolonged exposure may cause dermatitis.

#### Eye

##### Acute (Immediate)

- Causes eye irritation.

##### Chronic (Delayed)

- No data available.

#### Ingestion

##### Acute (Immediate)

- May cause irritation.

##### Chronic (Delayed)

- No data available.

#### Carcinogenic Effects

- This product contains carbon black (encapsulated)(1333-86-4). According to IARC "No significant exposure to carbon black is thought to occur during the use of products in which carbon black is bound to other materials, such as rubber, printing ink or paint."

Carcinogenic Effects		
	CAS	IARC
Carbon Black	1333-86-4	Group 2B-Possible Carcinogen

## Section 12 - Ecological Information

### 12.1 Toxicity

- Material data lacking.

### 12.2 Persistence and degradability

- No data available

### 12.3 Bioaccumulative potential

- Material data lacking.

### 12.4 Mobility in Soil

- Material data lacking.

### 12.5 Results of PBT and vPvB assessment

- PBT and vPvB assessment has not been carried out.

### 12.6 Other adverse effects

- No studies have been found.
- No data available.

### Ecological Fate

### 12.7 Other Information

- No data is available on the adverse effects of this material on the environment. Aquatic toxicity values are expected to be in the range of 1 - 10 mg/l based upon data from components and similar products.

## Section 13 - Disposal Considerations

### 13.1 Waste treatment methods

#### Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

#### Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	UN1133	Adhesives, containing a flammable liquid	NDA	II	NDA
TDG	UN1133	ADHESIVES containing flammable liquid	3	II	Marine Pollutant
IMO/IMDG	UN1133	ADHESIVES containing flammable liquid	3	II	Marine Pollutant

IATA/ICAO	UN1133	Adhesives containing flammable liquid	3	II	Acute Aquatic Toxicity, Chronic Aquatic Toxicity
-----------	--------	---------------------------------------	---	----	--

**14.6 Special precautions for user** • None specified.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** • This product is provided only in non-bulk containers.

## Section 15 - Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** • Acute, Fire

State Right To Know				
Component	CAS	MA	NJ	PA
Naphtha (petroleum), hydrotreated light	64742-49-0	No	No	No
Heptane	142-82-5	Yes	Yes	Yes
3-Methylhexane	589-34-4	Yes	Yes	Yes
Methylcyclohexane	108-87-2	Yes	Yes	Yes
Hexane, 2-methyl-	591-76-4	Yes	No	Yes
Carbon Black	1333-86-4	Yes	Yes	Yes
3-Ethylpentane	617-78-7	No	No	No
Pentane, 2,3-dimethyl-	565-59-3	Yes	Yes	Yes
Zinc oxide	1314-13-2	Yes	Yes	Yes
Fuels, diesel, No. 2	68476-34-6	No	Yes	No
Calcium silicate	1344-95-2	Yes	Yes	Yes
Benzanilide, 2',2''-dithiobis-	135-57-9	No	No	No
Kaolin	1332-58-7	Yes	Yes	Yes
Propionic acid	79-09-4	Yes	Yes	Yes
Tall oil pitch	8016-81-7	No	No	No
Rosin oil	68425-08-1	No	No	No
Toluene	108-88-3	Yes	Yes	Yes
Tall oil	8002-26-4	No	No	No
Stearic acid	57-11-4	No	No	No
Benzene	71-43-2	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Yes	Yes

Inventory						
Component	CAS	Canada DSL	Canada NDSL	China	EU EINECS	EU ELNICS
Naphtha (petroleum), hydrotreated light	64742-49-0	Yes	No	Yes	Yes	No
Heptane	142-82-5	Yes	No	Yes	Yes	No
3-Methylhexane	589-34-4	No	Yes	Yes	Yes	No
Methylcyclohexane	108-87-2	Yes	No	Yes	Yes	No
Hexane, 2-methyl-	591-76-4	Yes	No	Yes	Yes	No
Carbon Black	1333-86-4	Yes	No	Yes	Yes	Yes
3-Ethylpentane	617-78-7	No	No	Yes	Yes	No
Pentane, 2,3-dimethyl-	565-59-3	No	Yes	Yes	Yes	No
Zinc oxide	1314-13-2	Yes	No	Yes	Yes	No
Fuels, diesel, No. 2	68476-34-6	Yes	No	Yes	Yes	No
Calcium silicate	1344-95-2	Yes	No	Yes	Yes	No
Benzanilide, 2',2''-dithiobis-	135-57-9	Yes	No	Yes	Yes	No
Kaolin	1332-58-7	Yes	No	Yes	Yes	No
Propionic acid	79-09-4	Yes	No	Yes	Yes	No
Tall oil pitch	8016-81-7	Yes	No	Yes	Yes	No
Rosin oil	68425-08-1	Yes	No	No	Yes	No
Toluene	108-88-3	Yes	No	Yes	Yes	No
Tall oil	8002-26-4	Yes	No	Yes	Yes	No
Stearic acid	57-11-4	Yes	No	Yes	Yes	No
Benzene	71-43-2	Yes	No	Yes	Yes	No
Ethylbenzene	100-41-4	Yes	No	Yes	Yes	No

Inventory (Con't.)				
Component	CAS	Japan ENCS	Korea KECL	TSCA
Naphtha (petroleum), hydrotreated light	64742-49-0	No	Yes	Yes
Heptane	142-82-5	Yes	Yes	Yes
3-Methylhexane	589-34-4	Yes	Yes	Yes
Methylcyclohexane	108-87-2	Yes	Yes	Yes
Hexane, 2-methyl-	591-76-4	Yes	Yes	Yes
Carbon Black	1333-86-4	Yes	Yes	Yes
3-Ethylpentane	617-78-7	Yes	Yes	No
Pentane, 2,3-dimethyl-	565-59-3	Yes	Yes	Yes
Zinc oxide	1314-13-2	Yes	Yes	Yes
Fuels, diesel, No. 2	68476-34-6	No	Yes	Yes
Calcium silicate	1344-95-2	Yes	Yes	Yes
Benzanilide, 2',2''-dithiobis-	135-57-9	Yes	Yes	Yes

Kaolin	1332-58-7	Yes	Yes	Yes
Propionic acid	79-09-4	Yes	Yes	Yes
Tall oil pitch	8016-81-7	Yes	Yes	Yes
Rosin oil	68425-08-1	No	Yes	Yes
Toluene	108-88-3	Yes	Yes	Yes
Tall oil	8002-26-4	Yes	Yes	Yes
Stearic acid	57-11-4	Yes	Yes	Yes
Benzene	71-43-2	Yes	Yes	Yes
Ethylbenzene	100-41-4	Yes	Yes	Yes

## Canada

### Labor

#### Canada - WHMIS - Classifications of Substances

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Uncontrolled product according to WHMIS classification criteria
• Stearic acid	57-11-4	0.0022%	Uncontrolled product according to WHMIS classification criteria
• Tall oil	8002-26-4	0.0352%	Uncontrolled product according to WHMIS classification criteria
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	B2
• 3-Methylhexane	589-34-4	0% TO 24.888%	B2
• Hexane, 2-methyl-	591-76-4	0% TO 15%	B2
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	D2A
• Propionic acid	79-09-4	0.0011% TO 0.0056%	B3, D1B, E
• Carbon Black	1333-86-4	1% TO 5%	D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Carbon Black, non-respirable on Health Canada's WHMIS website.)
• Ethylbenzene	100-41-4	< 0.001%	B2, D2A, D2B
• Heptane	142-82-5	24.888% TO 37.332%	B2, D2B
• Toluene	108-88-3	< 0.05%	B2, D2A, D2B
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Uncontrolled product according to WHMIS classification criteria
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	B2, D2A, D2B
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	B2
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### Canada - WHMIS - Ingredient Disclosure List

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	1 %
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed



• Methylcyclohexane	108-87-2	0% TO 20%	1 %
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	1 %
• Carbon Black	1333-86-4	1% TO 5%	1 %
• Ethylbenzene	100-41-4	< 0.001%	0.1 %
• Heptane	142-82-5	24.888% TO 37.332%	1 %
• Toluene	108-88-3	< 0.05%	1 %
• Zinc oxide	1314-13-2	0.5% TO 1.5%	1 %
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	0.1 %
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## Environment

### Canada - CEPA - Priority Substances List

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Priority Substance List 1 (substance not considered toxic)
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Priority Substance List 1 (substance considered toxic)
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## Europe

### Other

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Carc.Cat.3; R40
------------------------	------------	--------------	-----------------

• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65
• Methylcyclohexane	108-87-2	0% TO 20%	F; R11 Xi; R38 N; R51 R53 Xn; R65 R67
• 3-Methylhexane	589-34-4	0% TO 24.888%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• Hexane, 2-methyl-	591-76-4	0% TO 15%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	C; R34
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	F; R11 Xn; R20
• Heptane	142-82-5	24.888% TO 37.332%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• Toluene	108-88-3	< 0.05%	F; R11 Xi; R38 Xn; R48/20 R65 Repr.Cat.3; R63 R67
• Zinc oxide	1314-13-2	0.5% TO 1.5%	N; R50 R53
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	F; R11 Xi; R36/38 Carc.Cat.1; R45 Muta.Cat.2; R46 T; R48/23/24/25 Xn; R65
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
• 3-Ethylpentane	617-78-7	0% TO 5%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	25%<=C: C; R34 10%<=C<25%: Xi; R36/37/38
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Xn R:40 S:(2)-36/37
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	T R:45-46-65 S:53-45
• Methylcyclohexane	108-87-2	0% TO 20%	F Xn N R:11-38-51/53-65-67 S:(2)-9-16-33-61-62
• 3-Methylhexane	589-34-4	0% TO 24.888%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
• Hexane, 2-methyl-	591-76-4	0% TO 15%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	C R:34 S:(1/2)-23-36-45
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	F Xn R:11-20 S:(2)-16-24/25-29
• Heptane	142-82-5	24.888% TO 37.332%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
• Toluene	108-88-3	< 0.05%	F Xn R:11-38-48/20-63-65-67 S:(2)-36/37-46-62
• Zinc oxide	1314-13-2	0.5% TO 1.5%	N R:50/53 S:60-61
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	F T R:45-46-11-36/38-48/23/24/25-65 S:53-45
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
• 3-Ethylpentane	617-78-7	0% TO 5%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	H
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	H, P
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	C
• Hexane, 2-methyl-	591-76-4	0% TO 15%	C
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	B
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	C
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	E
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	C
• 3-Ethylpentane	617-78-7	0% TO 5%	C

#### EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	S:(2)-36/37
------------------------	------------	--------------	-------------

• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	S:53-45
• Methylcyclohexane	108-87-2	0% TO 20%	S:(2)-9-16-33-61-62
• 3-Methylhexane	589-34-4	0% TO 24.888%	S:(2)-9-16-29-33-60-61-62
• Hexane, 2-methyl-	591-76-4	0% TO 15%	S:(2)-9-16-29-33-60-61-62
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	S:(1/2)-23-36-45
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	S:(2)-16-24/25-29
• Heptane	142-82-5	24.888% TO 37.332%	S:(2)-9-16-29-33-60-61-62
• Toluene	108-88-3	< 0.05%	S:(2)-36/37-46-62
• Zinc oxide	1314-13-2	0.5% TO 1.5%	S:60-61
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	S:53-45
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	S:(2)-9-16-29-33-60-61-62
• 3-Ethylpentane	617-78-7	0% TO 5%	S:(2)-9-16-29-33-60-61-62

## United States

### Labor

#### U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - OSHA - Specifically Regulated Chemicals

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	5 ppm STEL (Cancer hazard, Flammable, See 29 CFR 1910.1028, 15 min); 0.5 ppm Action Level; 1 ppm TWA
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## Environment

### U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	(including Benzene from gasoline)
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

**U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities**

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	5000 lb final RQ; 2270 kg final RQ
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	1000 lb final RQ; 454 kg final RQ
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	1000 lb final RQ; 454 kg final RQ
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	10 lb final RQ (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule); 4.54 kg final RQ (received an adjusted RQ of 10 lbs based on potential carcinogenicity in an August 14, 1989 final rule)
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

**U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities**

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• Rosin oil	68425-08-1	0.0581%	Not Listed

● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed

● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

**U.S. - CERCLA/SARA - Section 313 - Emission Reporting**

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	0.1 % de minimis concentration
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	1.0 % de minimis concentration
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	1.0 % de minimis concentration (Chemical Category N982)
● Benzene	71-43-2	< 0.001%	0.1 % de minimis concentration
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

**U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing**

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	Not Listed
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	Not Listed
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed



• 3-Ethylpentane 617-78-7 0% TO 5% Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - Basis for Listing - Appendix VII

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Included in waste stream: F039
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Included in waste streams: F005, F024, F025, F037, F038, F039, K085, K104, K105, K141, K142, K143, K144, K145, K147, K151, K159, K169, K171, K172
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - Constituents for Detection Monitoring

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	

• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - D Series Wastes - Max Conc of Contaminants for the Tox Characteristic

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	0.5 mg/L regulatory level
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - Hazardous Constituents - Appendix VIII to 40 CFR 261

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	waste number U220
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	waste number U019
• Rosin oil	68425-08-1	0.0581%	Not Listed

● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - List for Hazardous Constituents

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - Phase 4 LDR Rule - Universal Treatment Standards

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	0.057 mg/L (wastewater); 10 mg/kg (nonwastewater)
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	0.080 mg/L (wastewater); 10 mg/kg (nonwastewater)
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	0.14 mg/L (wastewater); 10 mg/kg (nonwastewater)
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed

● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - TSD Facilities Ground Water Monitoring

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
● Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
● 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - RCRA (Resource Conservation & Recovery Act) - U Series Wastes - Acutely Toxic Wastes & Other Hazardous Characteristics

● Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
● Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
● Stearic acid	57-11-4	0.0022%	Not Listed
● Tall oil	8002-26-4	0.0352%	Not Listed
● Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
● Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
● 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
● Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
● Tall oil pitch	8016-81-7	0.4127%	Not Listed
● Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
● Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
● Carbon Black	1333-86-4	1% TO 5%	Not Listed
● Ethylbenzene	100-41-4	< 0.001%	Not Listed
● Heptane	142-82-5	24.888% TO 37.332%	Not Listed
● Toluene	108-88-3	< 0.05%	waste number U220
● Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
● Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
● Benzene	71-43-2	< 0.001%	waste number U019 (Ignitable waste, Toxic waste)
● Rosin oil	68425-08-1	0.0581%	Not Listed
● Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed

• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## United States - California

### Environment

#### U.S. - California - Proposition 65 - Carcinogens List

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	carcinogen, initial date 2/21/03 (airborne, unbound particles of respirable size)
• Ethylbenzene	100-41-4	< 0.001%	carcinogen, initial date 6/11/04
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	carcinogen, initial date 2/27/87
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - California - Proposition 65 - Developmental Toxicity

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	developmental toxicity, initial date 1/1/91
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed

• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	developmental toxicity, initial date 12/26/97
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	7000 µg/day MADL (level represents absorbed dose)
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	24 µg/day MADL (oral); 49 µg/day MADL (inhalation)
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	54 µg/day NSRL (inhalation); 41 µg/day NSRL (oral)
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed

• Benzene	71-43-2	< 0.001%	6.4 µg/day NSRL (oral); 13 µg/day NSRL (inhalation)
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - California - Proposition 65 - Reproductive Toxicity - Female

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	female reproductive toxicity, initial date 8/7/09
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Not Listed
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - California - Proposition 65 - Reproductive Toxicity - Male

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	male reproductive toxicity, initial date 12/26/97

• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## United States - Pennsylvania

### Labor

#### U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	
• Zinc oxide	1314-13-2	0.5% TO 1.5%	(including fume)
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	
• Benzene	71-43-2	< 0.001%	
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

#### U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Not Listed
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Not Listed
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Not Listed
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Not Listed
• Carbon Black	1333-86-4	1% TO 5%	Not Listed
• Ethylbenzene	100-41-4	< 0.001%	Not Listed
• Heptane	142-82-5	24.888% TO 37.332%	Not Listed
• Toluene	108-88-3	< 0.05%	Not Listed



• Zinc oxide	1314-13-2	0.5% TO 1.5%	Not Listed
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## United States - Rhode Island

### Labor

#### U.S. - Rhode Island - Hazardous Substance List

• Fuels, diesel, No. 2	68476-34-6	0.1% TO 1.5%	Not Listed
• Calcium silicate	1344-95-2	0.2466% TO 0.2468%	Toxic
• Stearic acid	57-11-4	0.0022%	Not Listed
• Tall oil	8002-26-4	0.0352%	Not Listed
• Naphtha (petroleum), hydrotreated light	64742-49-0	60% TO 100%	Not Listed
• Methylcyclohexane	108-87-2	0% TO 20%	Toxic
• 3-Methylhexane	589-34-4	0% TO 24.888%	Not Listed
• Hexane, 2-methyl-	591-76-4	0% TO 15%	Not Listed
• Tall oil pitch	8016-81-7	0.4127%	Not Listed
• Kaolin	1332-58-7	0.016% TO 0.02%	Toxic
• Propionic acid	79-09-4	0.0011% TO 0.0056%	Toxic; Flammable
• Carbon Black	1333-86-4	1% TO 5%	Toxic
• Ethylbenzene	100-41-4	< 0.001%	Toxic; Flammable
• Heptane	142-82-5	24.888% TO 37.332%	Toxic; Flammable
• Toluene	108-88-3	< 0.05%	Toxic (skin); Flammable (skin)
• Zinc oxide	1314-13-2	0.5% TO 1.5%	Toxic
• Zinc oxide as Zinc compounds		0.5% TO 1.5%	Not Listed
• Benzene	71-43-2	< 0.001%	Toxic (skin); Flammable (skin); Carcinogen (skin)
• Rosin oil	68425-08-1	0.0581%	Not Listed
• Benzanilide, 2',2'''-dithiobis-	135-57-9	0.02% TO 0.024%	Not Listed
• Pentane, 2,3-dimethyl-	565-59-3	0% TO 4.148%	Not Listed
• 3-Ethylpentane	617-78-7	0% TO 5%	Not Listed

## 15.2 Chemical Safety Assessment

- No Chemical Safety Assessment has been carried out.

### Section 16 - Other Information

<b>Last Revision Date</b>	• 12/April/2012
<b>Preparation Date</b>	• 12/April/2012
<b>Disclaimer/Statement of Liability</b>	• The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstance of use. Vendor assumes no responsibility for injury to vendee or third

persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

**Key to abbreviations**

NDA = No data available.

---